


## Controller Card BK-AVR2560

### Short description

With the MTS Controller Card BK-AVR2560 you can control different components (like relays, attenuators, filters etc.) by a RS-232 interface.

The card is equipped with 4x RS-232 and can be optionally extended with external interface modules for USB, LAN and/or IEEE-488. There are 72 output lines existing selectable as TTL drivers or open collector (3x 3 ULN drivers). Further 8 TTL input lines are integrated for relays indication or connection of manual control buttons.

A special firmware with interface commands can be created to customers wishes on request.



### Technical data:

#### 1 Connections:

1.1 RS-232 interfaces	1x 9pole Sub-D male, 3x 10pole flat ribbon
1.2 Inputs	1x 14pole flat ribbon
1.3 Outputs	3x 26pole flat ribbon
1.4 Voltage supply	1x 96pole DIN 41612 connector, male

#### 2 General specifications:

2.1 Power supply	5 V DC
2.2 Power consumption primarily	125 mA typ.
2.3 Control interface	4x RS-232
2.4 Inputs	8x TTL
2.5 Outputs	72x selectable as TTL or 3x 3 ULN drivers (500 mA each); mixing assembly is possible (has to be defined with ordering)
2.6 Operating temperature	0 °C - +50 °C
2.7 Reference temperature for specifications	+25 °C

2.8 Dimensions (without connections)	Eurocard 8 TE x 3 HU x 100 mm (W x H x D)
2.9 Colour	Front side colourless anodized
2.10 Weight	0,2 kg

#### 3 Delivered parts:

Controller Card BK-AVR2560  
CD with operating manual

#### 4 Comments:

Warranty 12 months  
RoHS-compliant Yes

#### 5 Recommended accessories:

Control software  
External interface modules with LAN, IEEE-488 and/or USB  
Colour display with touch panel