

## Checklist for inquiries of Relay Switching Units

From:

**Company:** \_\_\_\_\_ **Place:** \_\_\_\_\_  
**Name:** \_\_\_\_\_ **Phone:** \_\_\_\_\_  
**E-Mail:** \_\_\_\_\_ **Date:** \_\_\_\_\_


This checklist will help us to manufacture your equipment according to your wishes. Please complete this form with the essential specifications. Don't fill in data which are not critical for your use. This enables us to find a customized solution with reduced costs.

### General Specifications:

<b>Interface</b>	<input checked="" type="checkbox"/> USB <input type="checkbox"/> Others ...	<input type="checkbox"/> LAN, IP address: ...	<input type="checkbox"/> IEEE-488, bus address: ...
<b>Manual control</b>	<input type="checkbox"/> with touch panel display	<input type="checkbox"/> without	<input type="checkbox"/> Others: ...
<b>RF-connectors</b>	<input type="checkbox"/> SMA <input type="checkbox"/> BNC	<input type="checkbox"/> N <input type="checkbox"/> Others: ...	<input type="checkbox"/> TNC
<b>Connections on front side</b>	<input type="checkbox"/> RF-connectors <input type="checkbox"/> Others	<input type="checkbox"/> Interface	<input type="checkbox"/> Mains supply connector
<b>Connections on rear side</b>	<input type="checkbox"/> RF-connectors <input type="checkbox"/> Others	<input type="checkbox"/> Interface	<input type="checkbox"/> Mains supply connector
<b>Case style</b>	<input type="checkbox"/> 84 TE table top case	<input type="checkbox"/> 19" rack-mount	<input type="checkbox"/> Others: ...
<b>Height</b>	<input type="checkbox"/> 3 HU (standard)	<input type="checkbox"/> Others: ...	
<b>Depth</b>	mm max.		
<b>Power supply</b>	<input type="checkbox"/> 100-240 V AC, 50-60 Hz	<input type="checkbox"/> Linear regulated power supply 220-240 V AC, 50 Hz	<input type="checkbox"/> Others: ...
<b>Special wishes</b>	<input type="checkbox"/> Control software <input type="checkbox"/> Other display design	<input type="checkbox"/> Control output for external components ...	<input type="checkbox"/> Interlock <input type="checkbox"/> Others: ...
<b>Quantity</b>	pieces		

### Specifications for the RF-Switches:

	Module 1	Module 2	Module 3	Module 4	Module 5
<b>Type of component</b>					
<b>Quantity</b>					
<b>In-/Outputs</b>					
<b>Frequency range</b>					
<b>Impedance</b>					
<b>RF-connector</b>					
<b>Input power max.</b>					



## Checklist for inquiries of Relay Switching Units

	Module 1	Module 2	Module 3	Module 4	Module 5
<b>Isolation min. (*)</b>					
<b>VSWR max. (*)</b>					
<b>Insertion loss max. (*)</b>					
<b>Special function (**)</b>					

(\*) only if required  
(\*\*) e.g. terminated, with indicator outputs, latching etc. As a standard, 1/2-relays (SPDT) and transfer relays (DPDT) have the function 'failsafe' and multi position relays (SP3T - SP14T) have the function 'normally open'.

*Comments:*

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---